



RECESSED SPOTLIGHT
4.1911

UNDERWATER

IP68



Article number	Lamps	Lumen	Light colour	Wattage	V/mA	Radation angle	[v]
VERSIONS: <u>ONLY</u> UNDERWATER OPERATION							
4.1911.00.11	24 POW-LED	5520 lm	6000K cold white	total 62 W	CV 12 V DC	30°-120° Multiflux	W82
4.1911.00.12	24 POW-LED	4560 lm	3000K warm white	total 62 W	CV 12 V DC	30°-120° Multiflux	
4.1911.00.13	24 POW-LED	5160 lm	4500K neutral white	total 62 W	CV 12 V DC	30°-120° Multiflux	



4.1911 | RETROFIT-INSERTION FOR 4.1900

FOR RETROFITTING IN EXISTING SWIMMING POOLS WITH EXISTING SPOTLIGHTS.

STAINLESS
STEEL V4A
1.4571
316Ti

ALU

POW-LED
INCL.

3.000 K
4.500 K
6.000 K

12 V-DC

CABLE
INCL.

max 3m

CE



- Retrofit insertion for installation in existing spotlights 4.1900 for retrofitting halogen to LED
- Entirely made of stainless steel 316Ti 1.4571 and high-quality anodized aluminum
- ...
- POW-LED white 12 V-DC
- light distribution especially for swimming pool lighting
- ...
- Delivered ready for connection with end cover
- Constant-current power source ordered separately

! NOTE

?

Replacement/exchange requires separate agreements.

⚙️ OPTIONS

- POW-LED monochrome, single colour in green, red, amber, turquoise, capriblue
- POW-LED RGB or RGB-W available

Power supplies		Technical details see from page 234.	
5.0670.01.72	Power supply, max 1 spotlights	5.0670.02.72	Power supply, max 2 spotlights
5.0670.01.72		5.0670.02.72	
5.0670.01.72		5.0670.02.72	
5.0670.04.72	Power supply, max 4 spotlights	5.0670.04.72	Power supply, max 4 spotlights
5.0670.04.72		5.0670.04.72	
5.0670.04.72		5.0670.04.72	