


# SAFETY TRANSFORMERS

The standard supply units for the operation of underwater lights are moulded safety transformers with separate windings, designed to comply with protection system IP65 and contamination class P2.



| Article number      | Wattage |           | Connection    | Dimensions                  | Protection system | Weight  | Cable         |
|---------------------|---------|-----------|---------------|-----------------------------|-------------------|---------|---------------|
| <b>5.0098.00.00</b> | 50 VA   | 1 x 50 W  | 12V-AC        | (A) 170 x (B) 130 x (C) 80  | IP65              | 2,4 kg  | with cable    |
| <b>5.0100.00.00</b> | 100 VA  | 2 x 50 W  | 12 V-AC       | (A) 170 x (B) 130 x (C) 80  | IP65              | 3,2 kg  | with cable    |
| <b>5.0101.00.00</b> | 150 VA  | 2 x 75 W  | 12 V-AC       | (A) 185 x (B) 130 x (C) 90  | IP65              | 3,6 kg  | with cable    |
| <b>5.0311.00.00</b> | 200 VA  | 2 x 100 W | 12 V-AC       | (A) 185 x (B) 130 x (C) 105 | IP65              | 4,0 kg  | with cable    |
| <b>5.0103.00.00</b> | 350 VA  | 2 x 175 W | 12 V-AC       | (A) 215 x (B) 170 x (C) 110 | IP65              | 6,7 kg  | without cable |
| <b>5.0107.00.00</b> | 600 VA  | 2 x 300 W | 12 V-AC       | (A) 230 x (B) 220 x (C) 120 | IP65              | 12,0 kg | without cable |
| <b>5.0109.00.00</b> | 900 VA  | 3 x 300 W | 12 V-AC       | (A) 335 x (B) 220 x (C) 145 | IP65              | 18,2 kg | without cable |
| <b>5.0411.00.00</b> | 200 VA  | 1 x 200 W | 12/13/14 V-AC | (A) 185 x (B) 130 x (C) 105 | IP65              | 4,0 kg  | without cable |
| <b>5.0421.00.00</b> | 400 VA  | 2 x 200 W | 12/13/14 V-AC | (A) 215 x (B) 170 x (C) 110 | IP65              | 8,5 kg  | without cable |
| <b>5.0310.00.01</b> | 150 VA  | 1 x 150 W | 24 V-DC       | (A) 220 x (B) 175 x (C) 115 | IP65              | 6,8 kg  | without cable |
| <b>5.0312.00.01</b> | 250 VA  | 1 x 250 W | 24 V-DC       | (A) 220 x (B) 175 x (C) 115 | IP65              | 7,8 kg  | without cable |
| <b>5.0313.00.01</b> | 600 VA  | 4 x 150 W | 24 V-DC       | (A) 270 x (B) 255 x (C) 145 | IP65              | 16,9 kg | without cable |
| <b>5.0314.00.01</b> | 400 VA  | 2 x 200 W | 24 V-DC       | (A) 270 x (B) 255 x (C) 145 | IP65              | 17,1 kg | without cable |
| <b>5.0106.00.01</b> | 600 VA  | 1 x 600 W | 28 V-DC       | (A) 330 x (B) 215 x (C) 140 | IP65              | 17,1 kg | without cable |
| <b>5.0410.00.01</b> | 200 VA  | 1 x 200 W | 30 V-DC       | (A) 220 x (B) 175 x (C) 120 | IP65              | 4,4 kg  | without cable |
| <b>5.0420.00.01</b> | 400 VA  | 2 x 200 W | 30 V-DC       | (A) 310 x (B) 215 x (C) 120 | IP65              | 7,6 kg  | without cable |