


# SAFETY TRANSFORMERS

The standard supply units for the operation of underwater lights are moulded safety transformers with separate windings, designed to comply with protection system IP65 and contamination class P2.



Article number	Wattage		Connection	Dimensions	Protection system	Weight	Cable
<b>5.0098.00.00</b>	50 VA	1 x 50 W	12V-AC	(A) 170 x (B) 130 x (C) 80	IP65	2,4 kg	with cable
<b>5.0100.00.00</b>	100 VA	2 x 50 W	12 V-AC	(A) 170 x (B) 130 x (C) 80	IP65	3,2 kg	with cable
<b>5.0101.00.00</b>	150 VA	2 x 75 W	12 V-AC	(A) 185 x (B) 130 x (C) 90	IP65	3,6 kg	with cable
<b>5.0311.00.00</b>	200 VA	2 x 100 W	12 V-AC	(A) 185 x (B) 130 x (C) 105	IP65	4,0 kg	with cable
<b>5.0103.00.00</b>	350 VA	2 x 175 W	12 V-AC	(A) 215 x (B) 170 x (C) 110	IP65	6,7 kg	without cable
<b>5.0107.00.00</b>	600 VA	2 x 300 W	12 V-AC	(A) 230 x (B) 220 x (C) 120	IP65	12,0 kg	without cable
<b>5.0109.00.00</b>	900 VA	3 x 300 W	12 V-AC	(A) 335 x (B) 220 x (C) 145	IP65	18,2 kg	without cable
<b>5.0411.00.00</b>	200 VA	1 x 200 W	12/13/14 V-AC	(A) 185 x (B) 130 x (C) 105	IP65	4,0 kg	without cable
<b>5.0421.00.00</b>	400 VA	2 x 200 W	12/13/14 V-AC	(A) 215 x (B) 170 x (C) 110	IP65	8,5 kg	without cable
<b>5.0310.00.01</b>	150 VA	1 x 150 W	24 V-DC	(A) 220 x (B) 175 x (C) 115	IP65	6,8 kg	without cable
<b>5.0312.00.01</b>	250 VA	1 x 250 W	24 V-DC	(A) 220 x (B) 175 x (C) 115	IP65	7,8 kg	without cable
<b>5.0313.00.01</b>	600 VA	4 x 150 W	24 V-DC	(A) 270 x (B) 255 x (C) 145	IP65	16,9 kg	without cable
<b>5.0314.00.01</b>	400 VA	2 x 200 W	24 V-DC	(A) 270 x (B) 255 x (C) 145	IP65	17,1 kg	without cable
<b>5.0106.00.01</b>	600 VA	1 x 600 W	28 V-DC	(A) 330 x (B) 215 x (C) 140	IP65	17,1 kg	without cable
<b>5.0410.00.01</b>	200 VA	1 x 200 W	30 V-DC	(A) 220 x (B) 175 x (C) 120	IP65	4,4 kg	without cable
<b>5.0420.00.01</b>	400 VA	2 x 200 W	30 V-DC	(A) 310 x (B) 215 x (C) 120	IP65	7,6 kg	without cable